

October 15, 2020 | Virtual Experience



Envoy on Kittens

Improving Developer and Maintainer Velocity

Itay Donanhirsh, Softkitteh LLC



Cats are important part of CS



WIRED STAFF

06.26.12 11:15 AM

Google's Artificial Brain Learns to Find Cat Videos

How much of the Internet is cats?

15 percent

But **cats** are more popular with online audiences. In fact, according to Bloomberg's The Magazine Trying to Bring the Web's **Cat** Obsession Offline, **cats** drive almost 15 percent of all Web traffic. There are also about 30 million Google searches per month for the search term "**cat**". Feb 26, 2015

About

Cloud-native high-performance edge/middle/service proxy





The need



When a project have a growing number of contributors, there are procedures that need to be set in place.

These procedures need to be enforced, and better yet, automated if possible.



The need



For contributors, some operations need to be performed under customized constraints, such allowing only some people assign people on issues/PR, informing about various procedures, and more.

For maintainers, automation can help with issue tracking, specialized approval policies, and enforcing various rules.

Traditional Approach



Internal App Custom GitHub App Internal App

That's not that simple...



Lots of things to take care of:

- Service maintenance
- Authentication
- Monitoring
- High Availability
- Secrets management
- Adapt to GitHub API changes
- Dealing with GitHub API... oddities.
- Preserving issue context




Traditional Approach



Internal App Custom GitHub App Internal App

Meow RepoKitteh!





Now it's simpler



Lots of things to take care of included:

- Service maintenance
- Authentication
- Monitoring
- High Availability
- Secrets management
- GitHub API changes
- Dealing with GitHub API... oddities.
- Preserving issue context



The right abstraction



There is no need to worry about intricate non-GitHub events related things. This is already done for you.

You only need to deal with the actual required business logic.

For that, the right abstraction is required.



Meow Starlark!





Starlark is fun



"Starlark is a language intended for use as a configuration language. It was designed for the Bazel build system, but may be useful for other projects as well" github.com/bazelbuild/starlark

Starlark allows for **deterministic** evaluation, **hermetic** execution and **parallel** evaluation.

This allows for a "jailed" low-cost/overhead "serverless" architecture where only Starlark code is executed. No containers required!

Starlark is easy



Starlark is a dialect of Python, with a few <u>differences</u>. These allow it to be deterministic, hermetic and concurrent.

RepoKitteh is using the excellent Starlark Go module: github.com/google/starlark-go.



How does it fit in




RepoKitteh GitHub App Engine Traces UI/FE Context Secrets

Demo Time!



Enforce BUG=NNN annotation in PR body



Batteries Included



RepoKitteh includes tooling and APIs for frequently needed capabilities:

- Secrets management
- Detailed debug output
- GitHub API access
- Fine grained permission model
- Modules with version pinning
- And more!



Meow World



₽ master - envoy / repokitteh.star


The root module is the entry point to everything repokitteh. The module is evaluated on every event.

Handlers | Commands



```
def _backport():
    github.issue_label('backport/review')
handlers.command(name='backport', func=_backport)
```

<u>handlers.command</u> registers a command handler that is executed on /slash-commands.



repokitteh.io/docs/ref/modules/#handlers.command repokitteh.io/docs/ref/modules/#github.issue_label

```
Modules - RepoKitteh
             repokitteh.io/docs/ref/modules/#github.issue_label
                                                                                                           Q
\equiv
github.issue_label(*labels,repo_owner,repo_name,issue_number):dict ¶
Add a label to an issue.
ARGUMENTS
 • *labels: list(str)
   repo_owner: str (default=from context) - Must be supplied as a keyword argument.

    repo_name: str (default=from context) - Must be supplied as a keyword argument.

 • issue_number: int (default=from context) - Must be supplied as a keyword argument.
RETURNS

    dict - Same as GitHub API.

REQUIRED PERMISSIONS
 • github_call(method=POST, path=repos/{repo_owner}/{repo_name}/issues/{issue_number}/labels)
EXAMPLES
     print(github.issue_label('wip', 'pending')[0]['id'])
SEE ALSO

    GitHub API Docs: Add labels to an issue
```

Handlers | Events



<u>github.com/repokitteh/modules/blob/master/wait.star</u>

```
def _pull_request(action, labels):
  if action != 'synchronize':
    return
  if _waiting_push_label in labels:
    github.issue_unlabel(_waiting_push_label)
  if _waiting_any_label in labels:
    github.issue_unlabel(_waiting_any_label)
handlers.issue_comment(func=_issue_comment)
```

Handlers can be registered on virtually any GitHub event. In this (partial) example, which is taken from a RepoKitteh Module, an handler is registered on GitHub's <u>pull-request</u> event, among others.

Handlers receive context when executed, depending on their parameters and type.

```
handlers.pull_request(func=_pull_request)
handlers.pull_request_review(func=_issue_comment)
handlers.pull_request_review_comment(func=_issue_comment)
```

repokitteh.io/docs/ref/modules/#handlers.pull request

Modules | use



```
use(
  "github.com/envoyproxy/envoy/ci/repokitteh/modules/ownerscheck.star"
  paths=[
     "owner": "envoyproxy/api-shepherds!".
     "path":
     "(api/envoy[\w/]*/(v1alpha\d?|v1|v2alpha\d?|v2))|(api/envoy/type/(matcher/)?\w+.proto)",
     "label": "v2-freeze",
     "allow_global_approval": False,
     "github_status_label": "v2 freeze violations",
     "owner": "envoyproxy/api-shepherds!",
     "path": "api/envoy/",
     "label": "api",
     "github_status_label": "any API change",
     "owner": "envoyproxy/api-watchers",
     "path": "api/envoy/",
     "owner": "envoyproxy/dependency-watchers",
     "path":
     "(bazel/repository_locations\.bzl)|(api/bazel/repository_locations\.bzl)|(.*/requirements\.txt)",
```

use loads a module and registers its handlers. A module is defined in its own file which can reside in github.

Configuration is supplied to the loaded module by using key-value parameters.

Some generic modules: github.com/repokitteh/modules

repokitteh.io/docs/ref/funcs/#use

Modules | use



```
handlers.command(name='checkowners', func=_reconcile)
def _get specs(config):
  return _get_relevant_specs(config.get('paths', []), github.pr_list_files())
def _reconcile(config, specs=None):
  specs = specs or _get_specs(config)
  if not specs:
    return []
```

```
load('text', 'match')

load("github.com/repokitteh/modules/lib/utils.star", "react")
load("github.com/repokitteh/modules/lib/circleci.star", "retry", "cancel")

m = match(text=target_url, pattern='/([0-9]+)\?')

if m and len(m) == 2:
    failed_builds.append((int(m[1]), target_url, context))
```

load is a Starlark builtin which brings in functions from other modules. It can be called from any module.

use is a RepoKitteh function that registers handlers from other modules. It can be called only from the root module.

<u>repokitteh.io/docs/ref/modules/#text.match</u> <u>github.com/google/starlark-go/blob/master/doc/spec.md#load-statements</u>

Issue Context Store



```
def _store_partial_approval(who, files):
    for f in files:
        store_put('ownerscheck/partial/%s:%s' % (who, f['filename']), f['sha'])

def _is_partially_approved(who, files):
    for f in files:
        sha = store_get('ownerscheck/partial/%s:%s' % (who, f['filename']))
        if sha != f['sha']:
            return True
```

store_put and store_read write and read data associates with the issue/PR in context. This can be used to store state for an issue/PR.

repokitteh.io/docs/ref/funcs/#store_get repokitteh.io/docs/ref/funcs/#store_put

Secrets



```
use("github.com/repokitteh/modules/circleci.star", secret_token=get_secret('circle_token'))
use("github.com/envoyproxy/envoy/ci/repokitteh/modules/azure_pipelines.star", secret_token=get_secret('azp_token'))
return http(secret_url=url, method='POST')
```

get secret can be called only from the root module.

repokitteh.io/docs/ref/funcs/#get_secret



Context & Tracing



repokitteh bot commented 3 days ago

CC @envoyproxy/dependency-watchers: FYI only for changes made to (bazel/repository_locations\.bzl)|
(api/bazel/repository_locations\.bzl)|(.*/requirements\.txt) .

▼
Caused by: #13364 was opened by rebello95.

see: more, trace.

```
Repository envoyproxy/envoy
Delivery-ID 874b6400-0428-11eb-8994-3d5b9f2dc65d
Event-Type github:pull_request
           https://github.com/envoy/proxy/envoy/pull/13364 was opened by rebello95. (link)
Reason
 Ingestion
             Evaluation
Version
                  0.41.4 46d1002d666d36ad2bdb0eb392a4d43a2c1a383b
Receive-Time
                  2020-10-01 20:56:08.948198023 +0000 UTC
HTTP-Response-Code 202
HTTP-Response-Text
processing
https://prod.repokitteh.app/traces/ui/envoyproxy/envoy/874b6400-0428-11eb-8994-3d5b9f2dc65d
▼ Event-Payload
    "action": "opened",
    "number": 13364,
    "pull_request": {
       "url": "https://api.github.com/repos/envoy/proxy/envoy/pulls/13364",
       "id": 496541591.
       "node id": "MDEx0lB1bGxSZXF1ZXN0NDk2NTQxNTkx",
       "html_url": "https://github.com/envoyproxy/envoy/pull/13364",
       "diff url": "https://github.com/envoyproxy/envoy/pull/13364.diff",
       "patch_url": "https://github.com/envoyproxy/envoy/pull/13364.patch",
       "issue_url": "https://api.github.com/repos/envoyproxy/envoy/issues/13364",
       "number": 13364,
       "state": "open",
       "locked": false,
       "title": "build: update abseil & enable -Wrange-loop-analysis".
       "user": {
          "login": "rebello95",
          "id": 2643476.
          "node id": "MDQ6VXNlcjI2NDM0NzY=",
          "avatar url": "https://avatars1.githubusercontent.com/u/2643476?v=4".
          "gravatar id": "".
```

```
Repository envoyproxy/envoy
Delivery-ID 874b6400-0428-11eb-8994-3d5b9f2dc65d
Event-Type github:pull_request
            https://github.com/envoyproxy/envoy/pull/13364 was opened by rebello95. (link)
Reason
 Ingestion
              Evaluation
Version
              0.41.4 46d1002d666d36ad2bdb0eb392a4d43a2c1a383b
Start-Time
              2020-10-01 20:56:08.949636468 +0000 UTC
End-Time
              2020-10-01 20:56:12.566362588 +0000 UTC
▼ Console
 specs: [struct(allow global approval = True, files = [{"additions": 3, "sha": "fc308b6b0689b5342e20eac9dde6dd7daa78174c", "filename": "ba
 reviews=[]
 approvers: []
 team dependency-watchers(4043948) = ["moderation", "asraa", "htuch"]
 struct(allow_global_approval = True, files = [{"additions": 3, "sha": "fc308b6b0689b5342e20eac9dde6dd7daa78174c", "filename": "bazel/repo
Commands
              Empty
▶ Pinned Refs
▶ Modules
▶ Calls
▶ Perms
▶ Context
```

```
▼ Context
   "action": "opened",
    "assignee": null,
    "assignees": [],
    "blessed": false.
    "branches": null,
    "commands": [],
    "comment": null.
    "comment id": null,
    "context": null.
    "delivery_id": "874b6400-0428-11eb-8994-3d5b9f2dc65d",
    "description": null,
    "draft": true,
    "event source": "github",
    "event_type": "pull_request",
    "head_repo_name": "envoy",
    "head_repo_owner": "rebello95",
    "is_pr": true,
   "issue_body": "**NOT READY FOR REVIEW, USING CI TO VALIDATE**\r\n\r\nRisk Level: Low\r\nTesting: CI\r\nDocs Changes: N/A\r\r
    "issue_number": 13364,
    "issue_title": "build: update abseil & enable -Wrange-loop-analysis",
   "issue_user": "rebello95",
    "labels": [].
    "merge commit sha": null,
    "merged": false,
    "pusher": null,
    "reason": {
       "description": "https://github.com/envoyproxy/envoy/pull/13364 was opened by rebello95.",
      "link": "https://github.com/envoyproxy/envoy/pull/13364"
   },
    "ref": "wrange",
    "ref_or_sha": "wrange",
   "repo_name": "envoy",
    "repo owner": "envoyproxy",
    "review_commit_id": null,
    "review id": null,
    "review_state": null,
    "sender": "rebello95",
   "sha": "75b5e65c9a1e728eb7a62d2d7076ccb71125a27b",
    "state": null.
    "target url": null,
    "trace_id": "envoyproxy/envoy/874b6400-0428-11eb-8994-3d5b9f2dc65d"
```

```
Repository envoyproxy/envoy
Delivery-ID 874b6400-0428-11eb-8994-3d5b9f2dc65d
Event-Type github:pull_request
            https://github.com/envoyproxy/envoy/pull/13364 was opened by rebello95. (link)
Reason
 Ingestion
              Evaluation
Version
              0.41.4 46d1002d666d36ad2bdb0eb392a4d43a2c1a383b
Start-Time
              2020-10-01 20:56:08.949636468 +0000 UTC
End-Time
              2020-10-01 20:56:12.566362588 +0000 UTC
▼ Console
 specs: [struct(allow global approval = True, files = [{"additions": 3, "sha": "fc308b6b0689b5342e20eac9dde6dd7daa78174c", "filename": "ba
 reviews=[]
 approvers: []
 team dependency-watchers(4043948) = ["moderation", "asraa", "htuch"]
 struct(allow_global_approval = True, files = [{"additions": 3, "sha": "fc308b6b0689b5342e20eac9dde6dd7daa78174c", "filename": "bazel/repo
Commands
              Empty
▶ Pinned Refs
▶ Modules
▶ Calls
▶ Perms
▶ Context
```

```
$use(
  "github.com/repokitteh/modules/circleci.star",
  secret_token="redacted",
) -> (
 null,
$get_secret(
  "azp_token",
) -> (
  "redacted",
$use(
  "github.com/envoyproxy/envoy/ci/repokitteh/modules/azure_pipelines.star",
  secret_token="redacted",
) -> (
 null,
$use(
  "github.com/envoyproxy/envoy/ci/repokitteh/modules/ownerscheck.star",
  paths=[{"allow_global_approval":false,"github_status_label":"v2 freeze violations","label":"v2-freeze","owner":"envoyproxy/api-shepherd
) -> (
 null,
github_call(
  method="GET",
 path="repos/envoyproxy/envoy/pulls/13364/files?page=1\u0026",
 body=null,
  success_codes=[200,201],
 accept=null,
) -> (
  {"body":"[{\"sha\":\"068b7c6af70bb5419f8dcc71914db0f3a8a11457\",\"filename\":\"bazel/envoy_internal.bzl\",\"status\":\"modified\",\"add
 null,
```

```
Repository envoyproxy/envoy
Delivery-ID 874b6400-0428-11eb-8994-3d5b9f2dc65d
Event-Type github:pull_request
           https://github.com/envoyproxy/envoy/pull/13364 was opened by rebello95. (link)
Reason
 Ingestion
              Evaluation
Version
              0.41.4 46d1002d666d36ad2bdb0eb392a4d43a2c1a383b
Start-Time
             2020-10-01 20:56:08.949636468 +0000 UTC
End-Time
              2020-10-01 20:56:12.566362588 +0000 UTC
▼ Console
 specs: [struct(allow global approval = True, files = [{"additions": 3, "sha": "fc308b6b0689b5342e20eac9dde6dd7daa78174c", "filename": "ba
 reviews=[]
 approvers: []
team dependency-watchers(4043948) = ["moderation", "asraa", "htuch"]
 struct(allow_global_approval = True, files = [{"additions": 3, "sha": "fc308b6b0689b5342e20eac9dde6dd7daa78174c", "filename": "bazel/repo
Commands
              Empty
▶ Pinned Refs
▶ Modules
▶ Calls
▶ Perms
▶ Context
```

github.com/repokitteh/modules/ → 4ee2ed0c3622aad7fcddc04cb5dc866e44a541e6 ▼ Modules github.com/repokitteh/modules/assign.star (repokitteh/modules#4ee2ed0c3622aad7fcddc04cb5dc866e44a541e6) github.com/repokitteh/modules/lib/utils.star (repokitteh/modules#4ee2ed0c3622aad7fcddc04cb5dc866e44a541e6) github.com/repokitteh/modules/review.star (repokitteh/modules#4ee2ed0c3622aad7fcddc04cb5dc866e44a541e6)

github.com/repokitteh/modules/wait.star (repokitteh/modules#4ee2ed0c3622aad7fcddc04cb5dc866e44a541e6)
github.com/repokitteh/modules/circleci.star (repokitteh/modules#4ee2ed0c3622aad7fcddc04cb5dc866e44a541e6)
github.com/repokitteh/modules/lib/circleci.star (repokitteh/modules#4ee2ed0c3622aad7fcddc04cb5dc866e44a541e6)

github.com/envoyproxy/envoy/ci/repokitteh/modules/azure_pipelines.star github.com/envoyproxy/envoy/ci/repokitteh/modules/ownerscheck.star

▼ Pinned Refs

Repokitteh in Envoy



Documentation: envoy/source/docs/repokitteh.md

Root module: <u>envoy/repokitteh.star</u>

Envoy specific modules: envoy/ci/repokitteh/modules

Available Commands:

- /assign & /review
- /retest & /retest-circle
- /wait & /wait-any
- /backport

Also custom made ownerscheck.

GitHub Actions



GitHub Actions essentially supply the same functionality.

The difference is that Actions are more optimized for long running processes, like CI and deployments. They are more resource intensive, and are generally more cumbersome to implement, as they require Docker and containerization, thus resulting in a slower turnaround time.

Repokitteh is optimized for short-running actions and enables much lower latency, faster turnaround time and lower cost.

RepoKitteh's Future



- GitLab Integration
- On-premise
- Improved UI
- Scripts Testing & GitHub Fake
- More documentation

Looking for more projects! repokitteh.io/waitlist

For more information...



repokitteh.io (Docs, Support)

Waitlist: repokitteh.io/waitlist

Lab: repokitteh.io/lab



Thank you!



Questions?

